

The following Notice is a true copy of a Notice on file in my office and all the parties mentioned therein except Selia Smith were present consenting to the Survey made in pursuance to said Notice. H. H. Hensley. M. C. Surveyor

Notice of Survey
Notice is hereby given to Selia Smith John Ballinger John Koons Sidney Smith Peter Bowers Simon May and J May That the county Surveyor of Monroe county will proceed on the 18th day of May 1875 to survey all the lines necessary to establish or perpetuate all the section quarter section and all other corners necessary to be perpetuated in section three (3) Township Seven (7) north Range two (2) west in said county. Said parties are notified to meet said surveyor at the North East corner of said section at one o'clock on said day. After the survey will be made in their absence (signed) Peter Ballinger

Notice came to hand May the 3rd 1875 served on Selia Smith, Simon May, John Ballinger J May Sidney Smith same day by reading and on Peter Bowers by reading on the 4th day of May 1875 served on John Koons by copy on the 4th day of May 1875 The within Notice was served by me the undersigned at the time and manner above mentioned May the 4th 1875 E. J. Morgan

In pursuance to Notice served in due form on the parties Surveyed for John Williams Robert Cowdree S. B. Wood and others on the 8th day of June 1875 The following lines for Section 26 Town 10 North Range 2 west commenced at the N.E. cor of said section Ran South $4\frac{1}{2}^{\circ}$ via 4000 to East $\frac{1}{2}$ m cor Ran the line from the centre of sec 25 in above named town & Range to centre of sec 26 and found the course to be $3^{\circ}17'$ from the magnetic bearing Dist 80.00 ch perpetuated the East $\frac{1}{2}$ m cor; corners Buck 14 in $S45^{\circ}W$ 36 L - Buck 12 in $N32\frac{1}{2}^{\circ}W$ - 25 L - Sugar 15 in $N9^{\circ}E$ - 57 L Commenced on the morning of 8th June on east sec line 72 L South of N.E. sec cor ran west 40 Rods set a stake measured thence north & set a stake perpetuated Ran thence the N.E. sec corner west 80 R & 14 L to cor Stone via 3° set a corner at the average distance being 40 R and $\frac{1}{2}$ L west of said N.E. cor of section within Elm 12 in $S83^{\circ}W$ - 49 L - Sycamore 6 in $N40^{\circ}W$ - 16 L. H. Hensley M. C. Surveyor